## PM400 - PM500 - PM1000

## PERMANENT MAGNET COVER LIFTER

Powerful magnets to be used in combination with folding levers APS90 - APS80, with trolley LK70, with mini excavators and cranes, for lifting very heavy ferrous manhole covers.





**Use 1:** necessary use in the presence of manhole covers excessively heavy or worn out.



Shownin picture PM500 lifting a steel plate weighing 300 Kg.



**PM500 - PM1000** can be used with mini excavators and cranes.

1 Ann		<b>6</b> )-
1	W. 1987	
2274	1 30 27 4	

Substantial increasing of lifting power.

TECHNICAL CHARACTERISTICS					
Model	Code	Weight	Dimensions (L x P x H)	Lifting weight*	
		Kg	cm	Kg	
PM400	K0458	9	20 x 9 x 9	400 (1200**)	
PM500	K0360	18	21 x 12 x 12	500 (1500**)	
PM1000	K0461	40	27 x 15 x 14	1000 (3000**)	

<sup>\*</sup> Attraction force tests performed on a C36 iron base with a thickness of 18 mm. The attraction forces may vary according to the thickness and material of the base to be lifted. Tolerance ± 5%.

\*\* The declared lifting force is, for a safety factor, only a third of that resulting from the test of strength carried out.

<sup>\*\*</sup>The declared lifting force is, for a safety factor, only a third of that resulting from the test of strength carried out. The magnets are industrial type whose lifting force has a triple safety margin of the weight of recommended lifting. ITALIFTERS magnets are to be used only for lifting manhole covers and the lifting height must never be greater than 30 cm from the road surface.

